

pronto®

THE SMART CHOICE FOR AUTO PARTS

TECH
PREFERRED

MOTOR OILS





MOTOR OILS

Pronto Motor Oil is formulated to exceed tough U.S. standards for outstanding protection and performance for today's sophisticated, hard working car and light truck engines.

Pronto Motor Oil contains a high quality, hydro treated paraffinic lubricating oil and a technologically advanced additive system which includes detergents, dispersants, viscosity improver, anti-wear and anti-friction agents, and oxidation and corrosion inhibitors.

Meets current ILSAC GF-5 SN performance requirements to give excellent protection against anti-wear, anti-oxidancy, ant-corrosively, better sludge control, and better TBN retention. Also meets Chrysler MS-6395 and GM 6094M specifications.

- Benefits include:
 - Reduced friction for excellent protection against engine wear and improved fuel economy
 - High resistance to viscosity and thermal breakdown
 - Fights volatility burn-off to minimize engine deposits and exhaust emissions
 - Great protection and performance
- High performance formulation for gasoline engines
- Guaranteed to meet or exceed warranty requirements for today's gasoline engines where specific motor oil is recommended by Original Equipment Manufacturer
- Engineered to extend engine life by reducing wear and preventing sludge build-up
- Designed to provide for easier cold-weather starting
- Always consult your owner's manual for specific recommendations

Typical Physical Properties of Pronto Full Synthetic Motor Oils								
Viscosity Grade	Method	Typical Results						
		5W-20	5W-30	10W-30	10W-40	20W-50	15W-40	HD30
		API SN/GF-5	API SN/GF-5	API SN/GF-5	API SN/GF-5	API SN	API CJ-4/SN	API SN
Specific Gravity at 60°F	ASTM D4052	0.8622	0.8627	0.8678	0.8725	0.8819	0.8770	0.8819
API Gravity	ASTM D287	32.62	32.52	31.56	30.68	28.95	29.85	28.95
Viscosity at 100°C, cSt	ASTM D445	8.71	10.87	10.20	15.86	17.87	15.61	11.35
Viscosity at 40°C, cSt	ASTM D445	52.10	66.60	64.52	112.30	164.70	118.8	95.81
Viscosity Index	ASTM D2270	145	154	145	150	120	138	105
ASTM Color	ASTM D1500	2.5	2.5	2.5	2.5	2.5	4	2.5
Cold Cranking Simulator, cP	ASTM D5293	6425	6427	4716	6539	8352	6087	-
Zinc, wt. %	ASTM D5185	0.085	0.085	0.085	0.085	0.085	-	0.085
Phosphorus, wt. %	ASTM D4951	0.072	0.072	0.072	0.072	0.072	-	0.072
Calcium, wt. %	ASTM D5185	0.214	0.214	0.214	0.214	0.214	-	0.214
Molybdenum, wt. %	ASTM D5185	0.008	0.008	0.008	0.008	0.008	-	0.008
Boron, wt. %	ASTM D5185	0.023	0.023	0.023	0.023	0.023	-	0.023
Sulfur, wt. %	ASTM D4951	0.295	0.309	0.319	0.294	0.320	-	0.283
Nitrogen, wt. %	ASTM D5762	0.102	0.102	0.102	0.102	0.102	-	0.102
Sulfated Ash, wt. %	ASTM D874	0.92	0.92	0.92	0.92	0.92	0.99	0.92