

# pronto®

The Smart Choice For Auto Parts

**TECH**  
**PREFERRED**

## SYNTHETIC BLEND MOTOR OIL





# SYNTHETIC BLEND MOTOR OIL

Pronto Synthetic Blend Motor Oil is formulated combining synthetic and conventional base oils and a high performance additive system. This combination provides increased protection for tough driving conditions that puts extra stress and demands on your engine. Better protection against sludge and varnish formation keeping your engine cleaner longer. Benefits include:

- Reduced friction for excellent protection against engine wear and improved fuel economy
- Better low-temperature and high-temperature protection than conventional oils
- Compatible with leading conventional and synthetic motor oils

## Typical Physical Properties of Pronto Synthetic Blend Motor Oils

	Method	Typical Results	
		5W-20	5W-30
<b>Viscosity Grade</b>		API SN/GF-5	API SN/GF-5
Specific Gravity at 60°F	ASTM D4052	0.8614	0.8611
API Gravity	ASTM D287	32.77	32.82
Viscosity at 100°C, cSt	ASTM D445	8.297	10.95
Viscosity at 40°C, cSt	ASTM D445	47.85	65.34
Viscosity Index	ASTM D2270	149	160
Pour Point °C (°F)	ASTM 5950	-45°C (-49°F)	-45°C (-49°F)
ASTM Color	ASTM D1500	2	2
Cold Cranking Simulator, cP	ASTM D5293	6062 (-30)	5779 (-30)
Zinc, % mass	ASTM D5185	0.085	0.085
Phosphorus, % mass	ASTM D4951	0.077	0.077
Calcium, % mass	ASTM D5185	0.25	0.25
Boron, % mass	ASTM D5185	0.018	0.018
Sulfur, % mass	ASTM D4951	0.298	0.298
Nitrogen, % mass	ASTM D5762	0.102	0.102
Sulfated Ash, % mass	ASTM D874	0.92	0.92